

www.SRCARIZONALLC.COM

# **MATERIAL SAFETY DATA BULLETIN**

Product and Company Identification
 Product name: Used Oily Water
 Supplier: SRC Arizona LLC
 5726 NW Market Street
 Glendale, AZ 85301
 Product and MSDS Information: (602) 819-6329

2. <u>Material Information</u>
Identity: Used Oily Water
Synonyms: Used Oil & Water Mixture; Wastewater
Family Chemical Name: Petroleum Hydrocarbon
NFPA Rating (scale 0 – 4): 0 – Health; 1 – Fire; 0 – Reactivity
MSDS Form No: Used Oil 081607

3. Hazards Identification

This material is a complex mixture of paraffinic, naphthenic and aromatic petroleum hydrocarbons that may contain one or more of the following: carbon deposits, sludge, aromatic and non-aromatic solvents, water (as a water-in-oil emulsion), glycols, wear etals and metallic salts, silicon-based antifoaming compounds, and miscellaneous lube-oil additive materials. This product fits the ACGIH definition for mineral-oil mist.

Typical Ingredients: Typical Volume %: CAS Number:

#### SRC ARIZONA LLC

#### Office & Facility Address – 5726 W. Market Street, Glendale, AZ 85301 Mailing Address - PO Box 26931, Phoenix, AZ 85068-6931

Used Oil 80 - 100 N/A Water 0 - 20 N/A Diesel Fuel 0 – 5 68476-34-6 / 64742-34-3 Gasoline 0-1 6474-46-4 Solvents 0 - 1 N/A Ethylene Glycol Trace – 3 107-21-1 Deposits and Sludge Trace -1 N/A Misc. Additive Compounds Trace -0.5 N/A Exposure Limits in Air Used Oil: Lig/Mist diesel Fuel: Liq/Mist Gasoline OSHA  $PEL - TWA (mg/M_3) NE / 5 NE / 5 NE$ OSHA PEL – STEL (mg/M3) NE / N/A NE / N/A NE ACGIH TLV – TWA (mg/M<sub>3</sub>) NE / 5 NE / 5 300 (ppm) ACGIH TLV – STEL (mg/M3) NE / 10 NE / 10 NE CAL OSHA – TWA (mg/M3) NE / 5 NE / 5 NE Note: NE = None Established; N/A = Not Applicable or Not Available

#### 4. First Aid Measures

Eye Contact: Immediately flush eyes with large amounts of water for a minimum of fifteen (15) minutes. If redness or irritation is present, continue flushing until the irritation subsides. If the material is hot, seek medical attention immediately for thermal burns.

Skin Contact: Wash contact area with soap and water. If clothing is contaminated, minimize contact time on skin by removing contaminated clothing (if applicable) and washing contact area thoroughly with soap and water. If material is hot, flush or submerge affected area in cold water, and seek medical attention immediately for thermal burns.

Inhalation: This material is of low vapor pressure and is not expected to present an inhalation exposure hazard at ambient conditions. If oil mist or aerosol is present, refer to section 8 (Exposure Controls/Personal Protection) of this document for appropriate preventative measures.

Ingestion: This material does not present an ingestion hazard if a very small quantity is accidentally swallowed. May act as a laxative. No treatment is necessary under

#### SRC ARIZONA LLC Office & Facility Address – 5726 W. Market Street, Glendale, AZ 85301 Mailing Address - PO Box 26931, Phoenix, AZ 85068-6931

ordinary circumstances. If cramping and/or diarrhea are present following ingestion, seek medical attention.

5. <u>Fire Protection and Fire-Fighting Measures</u> Flash Point: >200 F Test Method; ASTM D-92 (Cleveland Closed Cup)

Auto-Ignition Temp: 500 - 800 F, based on % volatile components. Test Method: E 659

Flammable Limits in Air (% by vol): Lower: < 1.0; Upper: 7.0

Extinguishing Media: Use dry chemical, foam, or carbon dioxide

Special Fire Fighting Procedures: Water may be ineffective, but can be used to cool containers exposed to heat of flame. Cautions should be exercised when using water or foam, as flash-steaming and/or frothing may occur, especially if sprayed directly into burning containers.

Special Protective Equipment: Use Self-Contained Breathing Apparatus (SCBA) in enclosed areas.

Unusual Fire and Explosion Hazards: Dense, irritating smoke may be generated at the site of the fire. Closed containers of used oil (e.g., 55-gallon drums) at the fire site may rupture and explode when exposed to heat. Use caution when closed, heated containers are present.

NFPA Hazard ID: Health: 0 Flammability: 1 Reactivity: 0

Hazardous Combustion Products: Carbon dioxide, Carbon Monoxide, and oxides of sulfur and phosphorus may be generated as products of combustion.

6. Accidental Release Measures

Notification Procedures: Immediately contact the local Fire Department, Police Department, and other appropriate authorities with (1) the time of the spill, (2) an estimate of the quantity spilled, and (3) the nature of the spill (locally contained or widespread). Stay calm at all time. In addition, contact the US Coast Guard National

#### SRC ARIZONA LLC

Office & Facility Address – 5726 W. Market Street, Glendale, AZ 85301 Mailing Address - PO Box 26931, Phoenix, AZ 85068-6931 Response Center at 1-800-424-8802 if a spill of any amount is made into or upon US navigable waterways, contiguous waterways, drainage ways, and/or adjoining shorelines.

Procedures if Material is Released or Spilled: Contain spill immediately. If possible, do not allow spill to enter sewers or watercourses. Remove all sources of ignition. Immediately apply an absorbent material such as sand, clay, diatomaceous earth, etc. to the spilled area. Large, voluminous spills may be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

Environmental Precautions: Disposal of collected material must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste – refer to state and local regulations. If regulated solvents are used to clean up spilled material, the resulting waste mixture may be regulated. Department of Transportation (DOT) regulations may apply for transporting this material. Materials should be recycled if possible.

Personal Precautions: Refer to section 3 (Hazards Identification), section 4 (First Aid Measures), section 8 (Exposure Controls/Personal Protection), and section 11 (Health Hazard Information) for necessary information.

#### 7. Handling and Storage

Handling: Keep away from heat, sparks, and flames. Avoid generating oil mists or aerosols.

Storage: Store in closed containers away from sources of heat and oxidizing chemicals. Do not store in, or transfer material to, unmarked containers. Always maintain Class 'B' fire extinguishers and keep readily available wherever this material is stored. See NFPA 30 and OSHA 1910.106 – flammable and Combustible Liquids. **This material is not classified as hazardous under DOT regulations.** 

#### 8. Exposure Controls/Personal Protection

Ventilation: If vapor or aerosol mist is generated when the material is heated or handled, adequate ventilation in accordance with Good Engineering Practice must be

#### SRC ARIZONA LLC Office & Facility Address – 5726 W. Market Street, Glendale, AZ 85301 Mailing Address - PO Box 26931, Phoenix, AZ 85068-6931

provided to maintain concentrations below the specified exposure or flammable limits.

Respiratory Protection: If oil mist or aerosol is present, use a NIOSH approved organic vapor respirator with an organic mist filter. Do not use compressed oxygen in hydrocarbon atmospheres.

Eye protection: Not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear a plastic face shield or splash-proof safety goggles.

Skin Protection: For prolonged and/or repeated exposures, wear impervious clothing (e.g., boots, gloves, aprons, smocks, etc.) over parts of the body subject to exposure. For hand protection, wear latex, nitrile rubber, neoprene, or equivalent gloves to prevent contact with the skin. Use barrier-specific protective creams to cover exposed skin that impervious clothing does not cover. If handling hot material, use insulated protective clothing (e.g., gloves, boots, etc.). All clothing should be properly laundered in hot water and detergent to remove traces of material. If clothing is disposable, overly contaminated, or cannot be decontaminated properly, (i.e., leather articles, including shoes). These should be properly disposed of in closed appropriate containers.

Exposure Limits: Caution should be exercised to not exceed the exposure limits listed in section (3) of this document.

9. Physical and Chemical Properties

Appearance: Dark, Viscous, oily liquid Color: Dark brown to black Odor: Pronounced hydrocarbon odor Odor Threshold – N/A PH: N/A Boiling Point: > 82 C (180 F) Melting Point: N/A Flash Point: > 200 F

#### SRC ARIZONA LLC

Office & Facility Address – 5726 W. Market Street, Glendale, AZ 85301 Mailing Address - PO Box 26931, Phoenix, AZ 85068-6931 Vapor Pressure – mmHg 20 C: < 0.1 Vapor Density: >1 (Air = 1) Evaporation Rate: 0.001 (Ether = 1) Density: 7.3 Lbs./Gal Specific Gravity, 60 F: 0.85 to 0.88 API Gravity, 60 F: 22 to 29 API Solubility in Water: Insoluble Pour Point: -12 C (10 F) Freezing Point: N/A Volatile Organic Compounds: < 2% (by vol) Note: N/A = Not Applicable; NE = Not established

10. <u>Stability and Reactivity</u> Stability (Thermal, Light, etc.): Stable

Conditions to Avoid: Avoid heat, flame, and contact with strong oxidizing agents.

Incompatibility (Materials to Avoid): Strong Oxidizers (e.g., peroxides, chromate, and permanganate compounds)

Hazardous Decomposition Products: Thermal decomposition products are highly dependent on the combustion conditions. A complex mixture of airborne solid, liquid, particulates, and gases will evolve when this material undergoes pyrolysis or combustion. Carbon monoxide and other unidentified organic compounds may be formed upon combustion.

Hazardous Polymerization: Will not occur under normal temperature and pressure conditions.

- 11. Health Hazard Information
- Acute Symptoms of Exposure

Inhalation: High concentrations of aerosol or mist may be generated at high temperatures and may be irritating to the respiratory tract, including nose and throat, and may cause difficulty breathing. This may be particularly true with people who have a high level of sensitivity and allergic reactions.

Skin: Prolonged and/or repeated exposure may cause mild skin irritation, including redness, burning, temporary drying, cracking, and acute dermatitis. Contact with hot material may cause thermal burns.

Eyes: Contact may cause slight to moderate irritation, including burning, redness, and tearing. Contact with hot material may cause thermal burns.

Ingestion: May cause mild irritation of the digestive tract, including cramping, diarrhea, nausea and vomiting. Aspiration into the lungs, by initial ingestion or vomiting, may cause mild to severe pulmonary injury.

### • Chronic Symptoms of Exposure

Inhalation: Exposure to high levels of oil mist concentration may lead to chronic pulmonary conditions such as chronic bronchitis, pneumonia, and emphysema.

Skin: Cracking, drying, and chronic dermatitis.

#### 12. <u>Statement of Carcinogenicity</u>

Used motor oil and some cutting oils are possible skin cancer hazards based on animal testing.

#### 13. <u>Disposal Considerations</u>

Waste Disposal: disposal of collected material must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste (refer to federal, state, and local regulations for regulated waste transport and disposal).

# 14. <u>Transport Information</u> **US DOT: This material is not classified as hazardous under DOT regulations**.

#### 15. <u>Regulatory Information</u>

Governmental Inventory Status (TSCA): Components of this material are listed in the TSCA inventory.

US Superfund Amendments and Reauthorization Act (SARA) Title III: This material contains toxic compounds of zinc and lead subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SARA (311/312) Reportable Hazard Categories:

## SRC ARIZONA LLC

Office & Facility Address – 5726 W. Market Street, Glendale, AZ 85301 Mailing Address - PO Box 26931, Phoenix, AZ 85068-6931 Immediate (Acute) Health Effects: No Delayed (Chronic) Health Effects: Yes Fire Hazard: No Sudden Release of Pressure Hazard: No Reactivity Hazard: No

16. Other Information

Use: Used Oil for Recycling; Processed Oil for On-Specification Used Fuel Oil

Legally required information is given in accordance with applicable regulations. Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and SRC Oil & Fuel disclaims all warranties or every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Nothing is intended as a recommendation for uses, which infringe valid patents, or as extending any license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Use or retransmission of the information contained herein in any other format than the format as presented is strictly prohibited. SRC Oil & Fuel neither represents nor warrants that the format, content, or product formulas contained in this document comply with the laws of any other country except the United States of America.

Revised December 20, 2016